

Portable Compressors

Mobilair™ M58 Utility



Versatile

The Mobilair™ M58 Utility rotary screw compressor is designed for cross mounting on service vehicles. It delivers 210 cfm at 100 psig and is ideal for public works, utility, and other field work vehicles.

User-friendly

The M58 Utility is very compact. It has both long and short side forklift slots as well as a single-point lifting bail for easy mounting/dismounting. The eye-level, curb side instrument panel features an easy to operate Sigma Control Smart electronic controller with protective metal cover. Another important feature is the

large 28 gallon fuel tank that provides extended operation - up to 10 full hours!

Efficient and Reliable

A heavy-duty 4-cylinder engine direct coupled to our energy saving Sigma Profile™ airend produces more air with less horsepower. A high capacity cold start battery ensures reliable operation even under extreme conditions.

The M58 Utility's rugged steel cabinet is powder-coated and built to take the harshest conditions while protecting the machine from dirt, water, and other contaminants.

The engine and compressor have separate inlet filters with maintenance indicators.

Standard Features:

- Sigma Profile™ rotary screw airend produces more air with less horsepower
- Heavy-duty 4-cylinder Kubota diesel engine meets Tier 4 Final EPA emissions standards
- Sigma Control Smart electronic controller
- Exclusive anti-frost valve maintains optimum operating temperature and prevents tool freeze up
- Large fuel tank for up to 10 hours of continuous operation
- Powder-coated steel cabinet
- High capacity cold start battery ensures reliable operation

Optional Features:

- Aftercooler package
- Pressures up to 145 psig

Optional 5 year warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airend.

This protection, combined with a high efficiency cooling system, allows the unit to operate in ambient temperatures up to 122°F.

Technical Specifications

COMPRESSOR			DIESEL ENGINE			PACKAGE			DIMENSIONS	
Model	Free Air Delivery (cfm)		Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L x W x H (in.)
	100 psig	145 psig								
M58 Utility	210	175	Kubota V2403-CR-E4B Tier 4 Final	48	2450 - 2600	1800	28	2043	2 x 3/4" 1 x 1"	84 5/8 x 33 1/8 x 55

Sound level maximum is 76 db(A) at 23 feet

Specifications subject to change without notice.

Outstanding Advantages

- ✓ Removable side panels and swing open end door
- ✓ Easy to operate Sigma Control Smart electronic controller
- ✓ Two 3/4" Chicago style fittings and one 1" NPT connection ports
- ✓ Short and long side fork slots for easy mounting
- ✓ Tier 4 Final Kubota diesel engine
- ✓ Energy saving Sigma Profile™ airend
- ✓ Extra large capacity fuel tank provides up to 10 full hours of operation
- ✓ Separate 4 micron air inlet filters protect compressor and engine
- ✓ Top exhaust port with rain cap
- ✓ Optional aftercooler package



KAESER COMPRESSORS®

Built for a lifetime.



www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Vérendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda.
Calz. Atanasio Tzul 21-00, zona 12
El Cortijo II, Bodega 501
01012-Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com

